Product Specification Sheet

DURACO

2811

Material Description: 2811 is a permanent tape with a tissue carrier. The adhesive is a high performance hot melt rubber based system and the liner is a black printed two sided silicone release paper with overlaps at each edge to give a "finger-lift" for easy liner removal. A general purpose hand tearable tape that is used for LSE surfaces, UV coatings, POP displays. Especially useful for many products produced by print finishers.

Product Information	Description	
Carrier	Tissue	
Adhesive	Rubber Based	
Release Liner	2.2 mils Silicone Release Liner	
Application Temperature (°F)	41 to 122	
Service Temperature (°F)	-4 to 149	
Adhesive and Carrier Thickness:	3.5 mils	
Adhesive	Typical Value	Test Method
Shear Resistance (minutes)	30	PSTC-107

1in², 72°F 10lb Load:		
90° Peel (lb/in):	8.5	PSTC-101
Quick Stick (lb/in):	5.2	PSTC-101

*Tests are performed on 2 mil PET

Food Contact Information

Based on supplier information the components of the adhesive conform to the compositional requirements of FDA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.

duraco.com

7400 Industrial Drive, Forest Park, IL 60130 | Phone: (866) 800-0775 | sales@duraco.com