## **Product Specification Sheet**



## **Duraco® Hook and Loop Low Profile**

**Material Description:** Duraco® Hook and Loop Low Profile fasteners have a rubber based adhesive with high initial tack, that has a slim profile that is up to 40% thinner than standard. The products come on a clear polyester liner for easy release. Ideal for low cycle applications.



Product Information	Description	
Material:	Nylon	
Color:	Black or White	
Adhesive	Rubber Based	
Release Liner	Clear Polyester Film	
Application Temperature (°F)	65 to 100	
Service Temperature (°F)	-5 to 150	
Adhesive	Typical Value	Test Method
90° Peel (lb/in):	8.0	PSTC-101

<sup>\*</sup>Tests are performed on 2 mil PET

## Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.

## duraco.com

7400 Industrial Drive, Forest Park, IL 60130 | Phone: (866) 800-0775 | sales@duraco.com