Product Specification Sheet



THICK REMO ONE® - 3/8" and 1/2"

Material Description: THICK REMO ONE® is a removable foam tape made to remove cleanly from most hard, non-delaminating surfaces even after exended periords of time. THICK REMO ONE® has a permanent adhesive on one side and a removable adhesive on the other side. Thicker foams can be used to create a 3-D effect.



Product Information	Description		
Carrier	Crosslinked Polyethylene		
Adhesive	Permanent - Rubber Based		
	Removable - Rubber Based		
Release Liner	Silicone coat		• •
Application Temperature (°F)	65 to 100		
Service Temperature (°F)	-20 to 150		
Thickness (inch)	0.375 and 0.500		
E	Tunical D	v o p o vti o o	Toot Mothed
Foam	Typical Properties		Test Method
Color:	White / Black		Visual
Density (lb/ft³):	2		ASTM D3575
Tensile Strength (psi) MD:	69		ASTM D3575
Tensile Strength (psi) CD:	42		
Elongation (% to break) MD:	136		
Elongation (% to break)CD:	111		ASTM D3575
Compression Deflection @25% (psi):	5		ASTM D3575
Compression Set @50% compression:	31		ASTM D3575
			T (NA () 1
Adhesive	Typical Value		Test Method
	Perm	Remo	
180° Peel Adhesion (lb/in)	8.0 min	2.5 min	PSTC-101
Shear Adhesion (hours): 1in², 10lb, 72°F	175.0 min	100.0 min	PSTC-107
Quick Stick (lb/in):	9.0 min	2.0 min	PSTC-5

^{*}Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.