

PVC MEDIUM DENSITY

High Flexibility + High Resistance

A permanent acrylic-based pressure sensitive adhesive that is a conformable, weather and oxidation resistant closed-cell foam.



FEATURES:

- Great barrier protection from moisture and air
- Excellent weather and oxidation resistance
- Excellent conformability
- Flexibility at low temperatures

APPLICATIONS:

- HVAC
- Appliance
- Construction
- General assembly
- RV/Trailer/Truck

SPECIFICATIONS:

- Test Method: ASTM D1667
- · Density (lb/ft3): Low: 7, Medium: 11
- · Compression Deflection: Low: 2 psi, Medium: 5 psi
- Compression Set (50%): Low: 8 max, Medium: 17 max
- Service Temperature: Low: -40°F to 180°F; Medium: -30°F to 200°F
- Flammability: FMVSS 302

duraco.com 866 800 0775

Can't find your size? We customize.



MEDIUM DENSITY ROLLS, GRAY

3" diameter core

Part Number	Thickness in	Width in	Length ft	Rolls/Carton
472113	1/16	1/2	150	20
472115	1/16	3/4	150	13
472114	1/16	1	150	10
472110	3/16	1/2	50	20
472111	3/16	3/4	50	13
472104	1/4	1/2	50	20
472109	1/2	1	25	10

NEED QUICK TURNAROUND?

Duraco manufactures and converts in-house, providing the convenient service of fast shipping and on-site tape experts. Contact us today.

*Roll diameter listed is nominal with a tolerance of +/- 6%.











LET'S TALK

duraco.com 866 800 0775